



An International Academic Journal Exploring Vehicle and Mobility Innovation

About *Automotive Innovation*

Aims & Scope

Sponsored by China SAE and published globally via Springer Nature, *Automotive Innovation* aims to be a world-class journal that provides abundant sources of innovative findings for automotive engineers and scientists. The journal is published quarterly, ensuring high-quality papers satisfying international standards. With the editorial board consisting of world-renowned experts, it has attracted readers from 72 countries and regions. The highest download of a single article wins more than 22,000. The journal is indexed in **Ei Compendex, ESCI, and SCOPUS**.

The journal is dedicated to the publication of peer-reviewed original papers and covers the principles, methodologies, designs, theoretical background and cutting-edge technologies in connection with the development of vehicle and mobility. The main topics include but are not limited to: energy-saving, electrification, intelligent and connected, safety and emerging technologies.

Submission online and read for free

www.ChinaSAEJournal.com.cn

www.springer.com/42154

Contacts

Jai-editor@sae-china.org

Articles Index

All articles published in the journal since 2018 are **listed according to the publication time** and **technical field** as below.

Articles Listed by Publication Time

Volume 6, Issue 1, 2023

[1] Zhao, Y., Geng, H., Liang, J. et al.: Effects of driver response time under take-over control based on CAR-ToC model in human-machine mixed traffic flow. *Automot. Innov.* **6**(1), 3–19 (2023)

<https://doi.org/10.1007/s42154-022-00207-y>

[2] Li, G., Wu, X., Eichberger, A. et al.: Drivers' EEG responses to different distraction tasks. *Automot. Innov.* **6**(1),

20–31 (2023)

<https://doi.org/10.1007/s42154-022-00206-z>

[3] Wu, Y., Zhang, J., Li, W. et al. Towards human-vehicle interaction: driving risk analysis under different driver vigilance states and driving risk detection method. *Automot. Innov.* **6**(1), 32–47 (2023)

<https://doi.org/10.1007/s42154-022-00209-w>

[4] Li, M., Jiang, C., Song, X. et al.: Parameter effects of the potential-field-driven model predictive controller for shared control. *Automot. Innov.* **6**(1), 48–61 (2023)

<https://doi.org/10.1007/s42154-022-00189-x>

[5] Kong, W., Cai, T., Luo, Y. et al.: Energy management optimization based on aging adaptive functional state model of battery for internal combustion engine vehicles. *Automot. Innov.* **6**(1), 62–75 (2023)

<https://doi.org/10.1007/s42154-022-00204-1>

[6] Wang, C., Jin, S., Deng, J. et al.: An innovative Argon/Miller power cycle for internal combustion engine: thermodynamic analysis of its efficiency and power density. *Automot. Innov.* **6**(1), 76–88 (2023)

<https://doi.org/10.1007/s42154-022-00208-x>

[7] Zhang, C., Huang, W., Niu, T. et al.: Review of clustering technology and its application in coordinating vehicle subsystems. *Automot. Innov.* **6**(1), 89–115 (2023)

<https://doi.org/10.1007/s42154-022-00205-0>

[8] He, Y., Jin, L., Guo, B. et al. Density-Based Road Segmentation Algorithm for Point Cloud Collected by Roadside LiDAR. *Automot. Innov.* **6**(1), 116–130 (2023)

<https://doi.org/10.1007/s42154-022-00212-1>

[9] Zhang, L., Ning, L., Yang, X. et al. Half-Power Prediction and Its Application on the Energy Management Strategy for Fuel Cell City Bus. *Automot. Innov.* **6**(1), 131–142 (2023)

<https://doi.org/10.1007/s42154-022-00210-3>

Volume 5, Issue 4, 2022

[1] Wang, J., Ma, F., Wu, L. et al.: Hybrid adaptive event-triggered platoon control with package dropout. *Automot. Innov.* **5**(4), 347–358 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00193-1>

[2] Chu, X., Xue, F., Liu, T. et al.: Adaptive fitting capacity prediction method for lithium-ion batteries. *Automot. Innov.* **5**(4), 359–375 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00201-4>

[3] Tian, C., Leng, B., Hou, X. et al.: Robust identification of road surface condition based on ego-vehicle trajectory reckoning. *Automot. Innov.* **5**(4), 376–387 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00196-y>

[4] Hengst, J., Werra, M. & Küçükay, F.: Evaluation of transmission losses of various battery electric vehicles. *Automot. Innov.* **5**(4), 388–399 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00194-0>

[5] Yang, S., Cheng, H., Wang, M. et al.: Multi-scale battery modeling method for fault diagnosis. *Automot. Innov.* **5**(4), 400–414 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00197-x>

[6] Yin, Y., Li, S.E., Tang, K. et al.: Approximate optimal filter design for vehicle system through Actor-Critic Reinforcement Learning. *Automot. Innov.* **5**(4), 415–426 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00195-z>

[7] Gao, M., Chen, L., Ma, T. et al.: Comparative study on traction battery charging strategies from the perspective of material structure. *Automot. Innov.* **5**(4), 427–437 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00199-9>

[8] Gao, Y., Yang, S., Wang, X. et al.: Cyber hierarchy multiscale integrated energy management of intelligent hybrid electric vehicles. *Automot. Innov.* **5**(4), 438–452 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00200-5>

[9] Guo, N., Zhang, X. & Zou, Y.: Real-time predictive control of path following to stabilize autonomous electric vehicles under extreme drive conditions. *Automot. Innov.* **5**(4), 453–470 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00202-3>

Volume 5, Issue 3, 2022

[1] Hoss, M., Scholtes, M. & Eckstein, L.: A Review of Testing Object-Based Environment Perception for Safe Automated Driving. *Automot. Innov.* **5**(3), 223–250 (2022)

<https://link.springer.com/article/10.1007/s42154-021-00172-y>

[2] Chen, W., Tian, W., Xie, X. et al.: RGB Image- and Lidar-Based 3D Object Detection Under Multiple Lighting Scenarios. *Automot. Innov.* **5**(3), 251–259 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00176-2>

[3] Jiang, K., Shi, Y., Zhou, T. et al.: PTMOT: A Probabilistic Multiple Object Tracker Enhanced by Tracklet Confidence for Autonomous Driving. *Automot. Innov.* **5**(3), 260–271 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00185-1>

[4] Wang, W., Yu, S., Cao, W. et al.: Review of In-Vehicle Optical Fiber Communication Technology. *Automot. Innov.* **5**(3), 272–284 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00184-2>

[5] Scheer, R., Bergheim, Y., Aleff, S. et al.: A Virtual Prototyping Approach for Development of PMSM on Real-Time Platforms: A Case Study on Temperature Sensitivity. *Automot. Innov.* **5**(3), 285–298 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00186-0>

[6] Zhang, P., Zhu, B., Zhao, J. et al.: Performance Evaluation Method for Automated Driving System in Logical Scenario. *Automot. Innov.* **5**(3), 299–310 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00191-3>

[7] Tong, Y., Li, C., Wang, G. et al. Integrated Path-Following and Fault-Tolerant Control for Four-Wheel Independent-Driving Electric Vehicles. *Automot. Innov.* **5**(3), 311–323 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00187-z>

[8] Sun, P., Wang, Y., He, P. et al. GCD-L: A Novel Method for Geometric Change Detection in HD Maps Using Low-Cost Sensors. *Automot. Innov.* **5**(3), 324–332 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00188-y>

[9] Zhang, B., Hao, D., Chen, J. et al. Modeling and Decentralized Predictive Control of Ejector Circulation-Based PEM Fuel Cell Anode System for Vehicular Application. *Automot. Innov.* **5**(3), 333–345 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00190-4>

Volume 5, Issue 2, 2022

- [1] Yang, N., Song, Z., Amini, M.R. et al.: Internal short circuit detection for parallel-connected battery cells using Convolutional Neural Network. *Automot. Innov.* **5**(2), 107–120 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00180-6>

- [2] Liu, K., Peng, Q., Li, K. et al.: Data-based interpretable modeling for property forecasting and sensitivity analysis of Li-ion battery electrode. *Automot. Innov.* **5**(2), 121–133 (2022)

<https://link.springer.com/article/10.1007/s42154-021-00169-7>

- [3] Huang, H., Meng, J., Wang, Y. et al.: An enhanced data-driven model for lithium-ion battery state-of-health estimation with optimized features and prior knowledge. *Automot. Innov.* **5**(2), 134–145 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00175-3>

- [4] Cao, R., Cheng, H., Jia, X. et al.: Non-invasive characteristic curve analysis of lithium-ion batteries enabling degradation analysis and data-driven model construction: a review. *Automot. Innov.* **5**(2), 146–163 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00181-5>

- [5] Wang, J., Gao, S., Qiang, Y. et al.: Structural topology and dynamic response analysis of an electric torque vectoring drive-axle for electric vehicles. *Automot. Innov.* **5**(2), 164–179 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00178-0>

- [6] Liu, Z., Zhang, W. & Zhao, F.: Impact, challenges and prospect of software-defined vehicles. *Automot. Innov.* **5**(2), 180–194 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00179-z>

- [7] Lu, H., Lu, C., Yu, Y. et al.: Autonomous overtaking for intelligent vehicles considering social preference based on hierarchical reinforcement learning. *Automot. Innov.* **5**(2), 195–208 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00177-1>

- [8] Wang, P., Xue, Q., Yang, J. et al.: Energy security planning for hydrogen fuel cell vehicles in large-scale events: a case study of Beijing 2022 Winter Olympics. *Automot. Innov.* **5**(2), 209–220 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00183-3>

Volume 5, Issue 1, 2022

- [1] Lin, C., Kong, W., Tian, Y. et al.: Heating lithium-ion batteries at low temperatures for onboard applications: recent progress, challenges and prospects. *Automot. Innov.* **5**(1), 3–17 (2022)

<https://link.springer.com/article/10.1007/s42154-021-00166-w>

- [2] Lin, C., Yu, X., Zhao, M. et al.: Collaborative control of novel uninterrupted propulsion system for all-climate electric vehicles. *Automot. Innov.* **5**(1), 18–28 (2022)

<https://link.springer.com/article/10.1007/s42154-021-00170-0>

- [3] Wang, Z., Li, L., Deng, J. et al.: Magnetic coupler robust optimization design for electric vehicle wireless charger based on improved simulated annealing algorithm. *Automot. Innov.* **5**(1), 29–42 (2022)

<https://link.springer.com/article/10.1007/s42154-021-00167-9>

- [4] Wijaya, B., Jiang, K., Yang, M. et al.: Crowdsourced road semantics mapping based on pixel-wise confidence level. *Automot. Innov.* **5**(1), 43–56 (2022)

<https://link.springer.com/article/10.1007/s42154-021-00173-x>

[5] Liu, Y., Chen, L., Cai, T. et al.: Dual-pump control algorithm of two-speed powershift transmissions in electric vehicles. *Automot. Innov.* **5**(1), 57–69 (2022)

<https://link.springer.com/article/10.1007/s42154-021-00160-2>

[6] Zhao, Y., Tian, W. & Cheng, H.: Pyramid Bayesian Method for model uncertainty evaluation of semantic segmentation in autonomous driving. *Automot. Innov.* **5**(1), 70–78 (2022)

<https://link.springer.com/article/10.1007/s42154-021-00165-x>

[7] Gao, F., Mu, J., Han, X. et al.: Performance limit evaluation strategy for automated driving systems. *Automot. Innov.* **5**(1), 79–90 (2022)

<https://link.springer.com/article/10.1007/s42154-021-00168-8>

[8] Wang, Y., Cao, X. & Ma, X.: Evaluation of automatic lane-change model based on vehicle cluster generalized dynamic system. *Automot. Innov.* **5**(1), 91–104 (2022)

<https://link.springer.com/article/10.1007/s42154-021-00171-z>

Volume 4, Issue 4, 2021

[1] Wu, X., Wang, J., Zhang, Y. et al.: Review of DC-DC converter topologies based on impedance network with wide input voltage range and high gain for fuel cell vehicles. *Automot. Innov.* **4**(4), 351–372 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00163-z>

[2] Meyer, M.A., Sauter, L., Granrath, C. et al.: Simulator coupled with distributed co-simulation protocol for automated driving tests. *Automot. Innov.* **4**(4), 373–389 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00161-1>

[3] Yurchenko, N.F., Breed, D.S., Zhang, S.: Design of the airbag inflation system applicable to conventional and autonomous vehicles. *Automot. Innov.* **4**(4), 390–399 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00156-y>

[4] Chen, G., Chen, K., Zhang, L. et al.: VCANet: vanishing-point-guided context-aware network for small road object detection. *Automot. Innov.* **4**(4), 400–412 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00157-x>

[5] Wen, X., Li, Y., Yang, C.: Design, modeling, and characterization of a tubular linear vibration energy harvester for integrated active wheel system. *Automot. Innov.* **4**(4), 413–429 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00144-2>

[6] Zhang, L., Meng, Q., Chen, H. et al.: Kalman Filter-based fusion estimation method of steering feedback torque for steer-by-wire systems. *Automot. Innov.* **4**(4), 430–439 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00159-9>

[7] Li, J., He, H., Wei, Z. et al.: Hierarchical sizing and power distribution strategy for hybrid energy storage system. *Automot. Innov.* **4**(4), 440–447 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00164-y>

[8] Huang, Y., Yang, S., Zhou, S. et al.: An innovative state-of-charge estimation method of lithium-ion battery based on 5th-order Cubature Kalman Filter. *Automot. Innov.* **4**(4), 448–458 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00162-0>

Volume 4, Issue 3, 2021

[1] Peng, L., Wang, H. & Li, J.: Uncertainty evaluation of object detection algorithms for autonomous vehicles. *Automot. Innov.* **4**(3), 241–252 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00154-0>

[2] Wang, Y., Wang, Y., Qin, H. et al.: A systematic risk assessment framework of automotive cybersecurity. *Automot. Innov.* **4**(3), 253–261 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00140-6>

[3] Zhang, D., Lv, C., Yang, T. et al.: Cyber-attack detection for autonomous driving using vehicle dynamic state estimation. *Automot. Innov.* **4**(3), 262–273 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00153-1>

[4] Quante, L., Zhang, M., Preuk, K. et al.: Human performance in critical scenarios as a benchmark for highly automated vehicles. *Automot. Innov.* **4**(3), 274–283 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00152-2>

[5] Liang, Y., Li, Y., Yu, Y. et al.: Path-following control of autonomous vehicles considering coupling effects and multi-source system uncertainties. *Automot. Innov.* **4**(3), 284–300 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00155-z>

[6] Biddle, L., Fallah, S.: A novel fault detection, identification and prediction approach for autonomous vehicle controllers using SVM. *Automot. Innov.* **4**(3), 301–314 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00138-0>

[7] Hu, J., Cai, S., Huang, T. et al.: Vehicle travel destination prediction method based on multi-source data. *Automot. Innov.* **4**(3), 315–327 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00136-2>

[8] Peng, B., Sun, Q., Li, S.E. et al.: End-to-end autonomous driving through dueling double Deep Q-Network. *Automot. Innov.* **4**(3), 328–337 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00151-3>

[9] Tang, J., Zhou, Q.: A computer graphics-based framework for 3D pose estimation of pedestrians. *Automot. Innov.* **4**(3), 338–349 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00142-4>

Volume 4, Issue 2, 2021

[1] Xue, Q., Yang, D., Jiang, L. et al.: Modifying carbon supports of catalyst for the oxygen reduction reaction in vehicle PEMFCs. *Automot. Innov.* **4**(2), 119–130 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00149-x>

[2] Du, L., Zhang, G. & Sun, S.: Proton Exchange Membrane (PEM) fuel cells with Platinum Group Metal (PGM)-free cathode. *Automot. Innov.* **4**(2), 131–143 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00146-0>

[3] Wang, H., Wang, R., Sui, S. et al.: Cathode design for Proton Exchange Membrane fuel cells in automotive applications. *Automot. Innov.* **4**(2), 144–164 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00148-y>

[4] Yin, C., Gao, Y., Li, K. et al.: Experimental investigation on local behaviors of PEMFC with segmented cell.

Automot. Innov. **4**(2), 165–175 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00145-1>

[5] Wu, G., Zhang, H., Xu, Y. et al.: Air-side fin geometry of a tube-strip heat exchanger for fuel cell vehicles. Automot. Innov. **4**(2), 176–188 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00147-z>

[6] Li, G., Liu, C., Wang, E. et al.: State of charge estimation for lithium-ion battery based on improved cubature kalman filter algorithm. Automot. Innov. **4**(2), 189–200 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00134-4>

[7] Bai, X., Chen, G., Li, W. et al.: Critical speeds of electric vehicles for regenerative braking. Automot. Innov. **4**(2), 201–214 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00143-3>

[8] Coratella, C., Parry, L., Li, Y. et al.: Experimental investigation of the rail pressure fluctuations correlated with fuel properties and injection settings. Automot. Innov. **4**(2), 215–226 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00133-x>

[9] Qin, Y., Zhao, Z., Wang, Z. et al.: Study of longitudinal–vertical dynamics for in-wheel motor-driven electric vehicles. Automot. Innov. **4**(2), 227–237 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00141-5>

Volume 4, Issue 1, 2021

[1] Cai, W., Wu, X., Zhou, M. et al.: Review and development of electric motor systems and electric powertrains for new energy vehicles. Automot. Innov. **4**(1), 3–22 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00139-z>

[2] Chen, H., Li, L. & Küçükay, F.: Study of series-parallel and power-split DHT for hybrid powertrains. Automot. Innov. **4**(1), 23–33 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00126-w>

[3] Xu, X., Liang, J., Hao, Q. et al.: A novel electric dual motor transmission for heavy commercial vehicles. Automot. Innov. **4**(1), 34–43 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00129-7>

[4] Wang, W., Zhang, Y., Sun, X. et al.: Model-based double closed-loop coordinated control strategy for the electro-mechanical transmission system of heavy power-split HEVs. Automot. Innov. **4**(1), 44–55 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00130-0>

[5] Qi, B., Yang, L., Zhang, L. et al.: Adaptive fault-tolerant control during the mode switching for electric vehicle dual-mode coupling drive system. Automot. Innov. **4**(1), 56–69 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00132-y>

[6] Dorsch, C., Wang, X. & Küçükay, F.: Objective rating of the launch behavior of conventional, hybrid and electric vehicles. Automot. Innov. **4**(1), 70–80 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00131-z>

[7] Wang, W., Durack, J.M., Durack, M.J. et al.: Automotive traction drive speed reducer efficiency testing. Automot. Innov. **4**(1), 81–92 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00135-3>

[8] Hu, J., Wei, Z. & He, H.: An online adaptive internal short circuit detection method of lithium-ion battery.

Automot. Innov. **4**(1), 93–102 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00127-9>

[9] Che, Y., Foley, A., El-Gindy, M. et al.: Joint estimation of inconsistency and state of health for series battery packs. Automot. Innov. **4**(1), 103–116 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00128-8>

Volume 3, Issue 4, 2020

[1] Li, B., Kuo, H., Wang, X. et al.: Thermal management of electrified propulsion system for low-carbon vehicles. Automot. Innov. **4**(3), 299–316 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00124-y>

[2] Yao, C., Dan, D., Zhang, Y. et al.: Thermal performance of a micro heat pipe array for battery thermal management under special vehicle-operating conditions. Automot. Innov. **4**(3), 317–327 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00114-0>

[3] Chen, Y., Yan, Y. & Li, B.: Thermal analyses of power electronics integrated with vapour chamber cooling. Automot. Innov. **4**(3), 328–335 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00123-z>

[4] Wang, G., Gao, Q., Yan, Y. et al.: Thermal management optimization of a lithium-ion battery module with graphite sheet fins and liquid cold plates. Automot. Innov. **4**(3), 336–346 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00121-1>

[5] Shen, M., Gao, Q.: Simulation and analysis of dual-evaporator refrigeration system for electric vehicles. Automot. Innov. **4**(3), 347–355 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00115-z>

[6] Shah, R.M.R.A., Qubeissi, M.A., McGordon, A. et al.: Micro gas turbine range extender performance analysis using varying intake temperature. Automot. Innov. **4**(3), 356–365 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00119-9>

[7] Zhao, Z., Liu, W., Li, F. et al.: Distributed gas ignition using injection strategy for high efficiency and clean combustion under lean condition. Automot. Innov. **4**(3), 366–373 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00116-y>

[8] Li, G., Li, S., Li, S. et al.: Deep reinforcement learning enabled decision-making for autonomous driving at intersections. Automot. Innov. **4**(3), 374–385 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00113-1>

[9] Chen, S., Chen, H. & Negrut, D.: Implementation of MPC-based path tracking for autonomous vehicles considering three vehicle dynamics models with different fidelities. Automot. Innov. **4**(3), 386–399 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00118-w>

Volume 3, Issue 3, 2020

[1] Rosenthal, S., Maaß, F., Kamaliev, M. et al.: Lightweight in automotive components by forming technology. Automot. Innov. **3**(3), 195–209 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00103-3>

[2] Sun, Y., Luzin, V., Duan, Y. et al.: Forming-induced residual stress and material properties of roll-formed high-strength steels. Automot. Innov. **3**(3), 210–220 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00112-2>

[3] Li, M., Wang, Y., Niu, Z. et al.: Study on the weld-bonding process optimization and mechanical performance of aluminum alloy joints. *Automot. Innov.* **3**(3), 221–230 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00106-0>

[4] Cui, J., Wang, S., Yuan, W. et al.: Effects of standoff distance on magnetic pulse welded joints between aluminum and steel elements in automobile body. *Automot. Innov.* **3**(3), 231–241 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00104-2>

[5] Ma, Y., Niu, S., Shan, H. et al.: Impact of stack orientation on self-piercing riveted and friction self-piercing riveted Aluminum alloy and Magnesium alloy joints. *Automot. Innov.* **3**(3), 242–249 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00108-y>

[6] Wang, D., Xie, C., Liu, Y. et al.: Multi-objective collaborative optimization for the lightweight design of an electric bus body frame. *Automot. Innov.* **3**(3), 250–259 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00105-1>

[7] Shi, Z., Chen, G., Zhu, L. et al.: Sandwich structure design of a cooling fin for battery modules against impact loads. *Automot. Innov.* **3**(3), 260–269 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00107-z>

[8] Li, J., Wang, L., Chen, Y. et al.: Research and application of lightweight index for passenger cars. *Automot. Innov.* **3**(3), 270–279 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00110-4>

[9] Lin, Y., Min, J., Teng, H. et al.: Flexural performance of steel–FRP composites for automotive applications. *Automot. Innov.* **3**(3), 280–295 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00109-x>

Volume 3, Issue 2, 2020

[1] Ma, F.W., Wang, J.W., Yang, Y., et al.: Stability design for the homogeneous platoon with communication time delay. *Automot. Innov.* **3**(2): 101–110 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00102-4>

[2] Hao, D., Wang, X.B., Zhang, Y.Y., et al.: Experimental study on hydrogen leakage and emission of fuel cell vehicles in confined spaces. *Automot. Innov.* **3**(2): 111–122 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00096-z>

[3] Mao, W.F., Yue, W., Pei, F., et al.: Manganese-based lithium-ion battery: Mn_3O_4 anode versus $LiNi_{0.5}Mn_{1.5}O_4$ cathode. *Automot. Innov.* **3**(2): 123–132 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00100-6>

[4] Xu, N., Yang, Y.Y., Guo, K.H.: A discrete tire model for cornering properties considering rubber friction. *Automot. Innov.* **3**(2): 133–146 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00097-y>

[5] Lei, Y.L., Song, P.X., Fu, Y.: Design of constant-speed control method for water medium hydraulic retarders based on neural network PID. *Automot. Innov.* **3**(2): 147–157 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00095-0>

[6] Ye, Z.S., Xie, W.D., Yin, Y.M., et al.: Dynamic rollover prediction of heavy vehicles considering critical frequency. *Automot. Innov.* **3**(2): 158–168 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00099-w>

[7] Noce, T., Hanriot, S.D.M., Sales, L.C.M., et al.: Energy conversion factor for gasoline engines in real-world

driving emission cycle. *Automot. Innov.* **3**(2): 169–180 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00098-x>

[8] Neumann, D., Schäfers, L., Muthyalu, P., et al.: Reduction of transient engine-out NO_x-emissions by advanced digital combustion rate shaping. *Automot. Innov.* **3**(2): 181–190 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00101-5>

Volume 3, Issue 1, 2020

[1] Liu, W.M., Yao, N.L., Shi, Y.W., et al.: Personality openness predicts driver trust in automated driving. *Automot. Innov.* **3**(1): 3–13 (2020)

<https://link.springer.com/article/10.1007/s42154-019-00086-w>

[2] Clark, J.R., Stanton, N.A., Revell, K.M.A.: Automated vehicle handover interface design: focus groups with learner, intermediate and advanced drivers. *Automot. Innov.* **3**(1): 14–29 (2020)

<https://link.springer.com/article/10.1007/s42154-019-00085-x>

[3] Allison, C.K., Stanton, N.A.: Constraining design: applying the insights of cognitive work analysis to the design of novel in-car interfaces to support eco-driving. *Automot. Innov.* **3**(1): 30–41 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00090-5>

[4] Brown, J. W. H., Stanton, N. A., Revell, K. M. A.: Usability assessment of steering wheel control interfaces in motorsport. *Automot. Innov.* **3**(1): 42–52 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00088-z>

[5] Terken, J., Pfleging, B.: Toward shared control between automated vehicles and users. *Automot. Innov.* **3**(1): 53–61 (2020)

<https://link.springer.com/article/10.1007/s42154-019-00087-9>

[6] Xue, W.Y., Zheng, L.: Active collision avoidance system design based on model predictive control with varying sampling time. *Automot. Innov.* **3**(1): 62–72 (2020)

<https://link.springer.com/article/10.1007/s42154-019-00084-y>

[7] Wang, Y. Y., Pan, D., Deng, H. Y., et al.: Dynamic trajectory planning of autonomous lane change at medium and low speeds based on elastic soft constraint of the safety domain. *Automot. Innov.* **3**(1): 73–87 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00091-4>

[8] Zhuang, W. C., Xu, L. W., Yin, G. D.: Robust cooperative control of multiple autonomous vehicles for platoon formation considering parameter uncertainties. *Automot. Innov.* **3**(1): 88–100 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00093-2>

Volume 2, Issue 4, 2019

[1] Yang, D., Jiao, X., Jiang, K. et al.: Driving space for autonomous vehicles. *Automot. Innov.* **2**(4): 241–253 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00081-1>

[2] Qin, Y., Wang, Z., Yuan, K. et al.: Comprehensive analysis and optimization of dynamic vibration-absorbing structures for electric vehicles driven by in-wheel motors. *Automot. Innov.* **2**(4): 254–262 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00079-9>

[3] Han, X., Feng, X., Ouyang, M. et al.: A comparative study of charging voltage curve analysis and state of health estimation of lithium-ion batteries in electric vehicle. *Automot. Innov.* **2**(4): 263–275 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00080-2>

[4] Cai, Y., Zhang, T., Wang, H. et al.: 3D vehicle detection based on LiDAR and camera fusion. *Automot. Innov.*

2(4): 276–283 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00083-z>

[5] Li, F., Wang, Z., Wang, Y. et al.: High-efficiency and clean combustion natural gas engines for vehicles. *Automot. Innov.* **2**(4): 284–304 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00075-z>

[6] Dong, G., Li, L., Zhu, D. et al.: Ion current features of HCCI combustion in a GDI engine. *Automot. Innov.* **2**(4): 305–313 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00074-0>

[7] Zhao, Z., Meng, Z., Li, L. et al.: Experimental study on the combustion and energy flows of vehicle engine under NEDC of cold start. *Automot. Innov.* **2**(4): 314–327 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00078-w>

[8] Liu, J., Huang, L., Zhou, R. et al.: Reliability growth test planning and verification of commercial vehicles. *Automot. Innov.* **2**(4): 328–337(2019)

<https://link.springer.com/article/10.1007/s42154-019-00082-0>

Volume 2, Issue 3, 2019

[1] Luo, Y., Yang, G., Xu, M., et al.: Cooperative lane-change maneuver for multiple automated vehicles on a highway. *Automot. Innov.* **2**(3), 157-168 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00073-1>

[2] Qin, D., Li, J., Wang, T., et al.: Modeling and simulating a battery for an electric vehicle based on modelica. *Automot. Innov.* **2**(3), 169-177 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00066-0>

[3] Ge, L., Ma, F., Shi, J., et al.: Numerical implementation of high-order Vold–Kalman filter using Python arbitrary-precision arithmetic library. *Automot. Innov.* **2**(3), 178-189 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00065-1>

[4] Wang, S., Guo, W., Zeng, K., et al.: Characterization of automotive brake discs with laser-machined surfaces. *Automot. Innov.* **2**(3), 190-200 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00068-y>

[5] Liu, X., Liang, M. & Luo, Q.: Innovative electric vehicle body design based on insurance institute for highway safety side impact conditions. *Automot. Innov.* **2**(3), 201-211 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00070-4>

[6] Tian, F., Sui, L., Zeng, Y., et al.: Hardware design and test of a gear-shifting control system of a multi-gear transmission for electric vehicles. *Automot. Innov.* **2**(3), 212-222 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00072-2>

[7] Wang, C., Lian, Y., Ling, H., et al.: Multiphysics field co-simulation research based on electric drive system for a specific type of car. *Automot. Innov.* **2**(3), 223-230 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00067-z>

[8] Li, L., Chen, H. & Küçükay, F.: Systematic synthesis of dedicated hybrid transmission. *Automot. Innov.* **2**(3), 231-239 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00071-3>

Volume 2, Issue 2, 2019

[1] Wu, Z., Zhao, W., Li, Z., et al.: A review of engine fuel injection studies using synchrotron radiation x-ray imaging. *Automot. Innov.* **2**(2), 79-92 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00056-2>

[2] Gao, Z., Li, Z., Hu, H., et al.: Experimental and numerical study of cervical muscle contraction in frontal impact. *Automot. Innov.* **2**(2), 93-101 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00060-6>

[3] Zhang, X., Huang, Y., Guo, K., et al.: Integrated spacing policy considering micro- and macroscopic characteristics. *Automot. Innov.* **2**(2), 102-109 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00064-2>

[4] Mimuro, T., Taniguchi, N. & Takanashi, H.: Concept study of a self-localization system for snow-covered roads using a four-layer laser scanner. *Automot. Innov.* **2**(2), 110-120 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00061-5>

[5] Yang, W.: Scale consistency quantification for subjective evaluation of vehicle dynamics. *Automot. Innov.* **2**(2), 121-126 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00062-4>

[6] Wang, D., Wen, J., Wang, Y., et al.: End-to-end self-driving using deep neural networks with multi-auxiliary tasks. *Automot. Innov.* **2**(2), 127-136 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00057-1>

[7] Qi, Y., Wang, B. & Wang, Z.: Impact resistance of spark plug's ceramic insulator during ultra-high-pressure combustion under deto-knock conditions. *Automot. Innov.* **2**(2), 137-145 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00058-0>

[8] Zhao, B., Lv, C. & Hofman, T.: Driving-cycle-aware energy management of hybrid electric vehicles using a three-dimensional Markov chain model. *Automot. Innov.* **2**(2), 146-156 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00059-z>

Volume 2, Issue 1, 2019

[1] Ma, F., Ying, Z., Wang, G., et al.: Crashworthiness optimization design of thin-walled tube filled with re-entrant triangles honeycombs. *Automot. Innov.* **2**(1), 1-13 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00051-7>

[2] Michelotti, A.C., da Silva, J.C., Nicolazzi, L.C.: Novel mechanical interface design for automotive starting systems. *Automot. Innov.* **2**(1), 14-25(2019)

<https://link.springer.com/article/10.1007/s42154-019-00052-6>

[3] Yang, W., Chen, J., Liu, Z., et al: Vibration characteristics of framed SUV cab based on coupled transfer path analysis. *Automot. Innov.* **2**(1) ,26-34(2019)

<https://link.springer.com/article/10.1007/s42154-019-00049-1>

[4] Zhu, M., Yao, P., Pu, Y.: Comparative study on the temperature rise of a dry dual clutch under different starting conditions. *Automot. Innov.* **2**(1), 35-44(2019)

<https://link.springer.com/article/10.1007/s42154-019-00053-5>

[5] Gong, H.: Estimation of residual exhaust gas of homogeneous charge compression ignition gasoline engine operating under negative valve overlap strategy. *Automot. Innov.* **2**(1), 45-54(2019)

<https://link.springer.com/article/10.1007/s42154-019-00048-2>

[6] Li, X., Lyu, J., Hong, J., et al.: MPC-based downshift control of automated manual transmissions. *Automot.*

Innov. 2(1), 55-63(2019)

<https://link.springer.com/article/10.1007/s42154-019-00050-8>

[7] Liu, J., Li, J., Wang, Y., et al.: Technology development analysis on low carbon for power of heavy-duty commercial vehicle. Automot. Innov. 2(1), 64-70(2019)

<https://link.springer.com/article/10.1007/s42154-019-00054-4>

[8] Shen, Q., Li, X., Zhao, Y., et al.: Experimental and performance analyses on elastomer-strengthened polyethylene terephthalate/glass fiber blends. Automot. Innov. 2(1), 71-78(2019)

<https://link.springer.com/article/10.1007/s42154-019-00047-3>

Volume 1, Issue 4, 2018

[1] Shi, T., Zhao, F., Hao, H., et al.: Development trends of transmissions for hybrid electric vehicles using an optimized energy management strategy. Automot. Innov. 1(4), 291-299(2018)

<https://link.springer.com/article/10.1007/s42154-018-0037-5>

[2] Xu, X., Sun, W., Cai, T., et al.: Design of a hydraulic control unit for a two-speed dedicated electric vehicle transmission. Automot. Innov. 1(4), 300-310(2018)

<https://link.springer.com/article/10.1007/s42154-018-0039-3>

[3] Qiu, L., Qian, L., Abdollahi, Z., et al.: Engine-map-based predictive fuel-efficient control strategies for a group of connected vehicles. Automot. Innov. 1(4), 311-319(2018)

<https://link.springer.com/article/10.1007/s42154-018-0042-8>

[4] Yu, C., Ji, G., Zhang, C., et al.: Cost-efficient thermal management for a 48v li-ion battery in a mild hybrid electric vehicle. Automot. Innov. 1(4), 320-330(2018)

<https://link.springer.com/article/10.1007/s42154-018-0043-7>

[5] Wu, J., Kang, Z., Zhang, Z., et al.: Effects of vessel and water temperatures on direct injection in internal combustion rankine cycle engines. Automot. Innov. 1(4), 331-341(2018)

<https://link.springer.com/article/10.1007/s42154-018-0046-4>

[6] Zhou, J., Feng, L., Chen, J., et al.: Uncertainty optimization design of a vehicle body structure considering random deviations. Automot. Innov. 1(4), 342-351(2018)

<https://link.springer.com/article/10.1007/s42154-018-0041-9>

[7] Gawande, S. H., MuleyR, A. A., Yerrawar, N.: Optimization of torsional stiffness for heavy commercial vehicle chassis frame. Automot. Innov. 1(4), 352-361(2018)

<https://link.springer.com/article/10.1007/s42154-018-0044-6>

[8] Guo, Y., Kumazawa, I., Kaku, C.: Blind spot obstacle detection from monocular camera images with depth cues extracted by CNN. Automot. Innov. 1(4), 362-373 (2018)

<https://link.springer.com/article/10.1007/s42154-018-0036-6>

[9] Chen, W., Lu, C., Liu, Z., et al.: Simplified method of simulating double-layer micro-perforated panel structure. Automot. Innov. 1(4), 374-380(2018)

<https://link.springer.com/article/10.1007/s42154-018-0040-x>

[10] Patel, T.M., Bhatt, N.M.: Optimizing neural network parameters using taguchi's design of experiments approach: an application for equivalent stress prediction model of automobile chassis. Automot. Innov. 1(4), 381-389(2018)

<https://link.springer.com/article/10.1007/s42154-018-0045-5>

Volume 1, Issue 3, 2018

[1] Xu, X., Dong, P., Liu, Y., et al.: Progress in automotive transmission technology. *Automot. Innov.* **1**(3), 187-210 (2018)

<https://link.springer.com/article/10.1007/s42154-018-0031-y>

[2] Lian, Y., Zeng, D., Ye, S., et al.: High-voltage safety improvement design for electric vehicle in rear impact. *Automot. Innov.* **1**(3), 211-225(2018)

<https://link.springer.com/article/10.1007/s42154-018-0030-z>

[3] Qin, D., Cheng, L., Wang, T., et al.: Modeling and testing of the multi-pole field of a motor for pure electric vehicles. *Automot. Innov.* **1**(3), 226-236 (2018)

<https://link.springer.com/article/10.1007/s42154-018-0025-9>

[4] Wang, S., Min, J., Lin, J., et al.: Effect of atmospheric pressure plasma treatment on the lap-shear strength of adhesive-bonded sheet molding compound joints. *Automot. Innov.* **1**(3), 237-246(2018)

<https://link.springer.com/article/10.1007/s42154-018-0027-7>

[5] Zheng, G., Fan, Z., Zhang, H., et al.: Crashworthiness optimization of steel–magnesium hybrid double-hat-shaped tube. *Automot. Innov.* **1**(3), 247-254 (2018)

<https://link.springer.com/article/10.1007/s42154-018-0033-9>

[6] Ou, H., Tang, X., Xiao, J., et al.: Lightweight body-in-white design driven by optimization technology. *Automot. Innov.* **1**(3), 255-262(2018)

<https://link.springer.com/article/10.1007/s42154-018-0032-x>

[7] Shao, X., Xu, N., Liu, X.: Investigation and application on the vertical vibration models of the seated human body. *Automot. Innov.* **1**(3), 263-271(2018)

<https://link.springer.com/article/10.1007/s42154-018-0026-8>

[8] Zhang, S.: Parameter study and improvement of gearbox whine noise in electric vehicle. *Automot. Innov.* **1**(3), 272-280(2018)

<https://link.springer.com/article/10.1007/s42154-018-0029-5>

[9] Pei, X., Hu, X., Liu, W., et al.: State estimation of vehicle's dynamic stability based on the nonlinear kalman filter. *Automot. Innov.* **1**(3), 281-289(2018)

<https://link.springer.com/article/10.1007/s42154-018-0028-6>

Volume 1, Issue 2, 2018

[1] Shuai, S., Ma, X., Li, Y., et al.: Recent progress in automotive gasoline direct injection engine technology. *Automot. Innov.* **1**(2), 95-113(2018)

<https://link.springer.com/article/10.1007/s42154-018-0020-1>

[2] Dong, Y., Chen, Y., Yu, C., et al.: Performance of the transmission parking mechanism of a battery electric vehicle simulated with Adams software. *Automot. Innov.* **1**(2), 114-121(2018)

<https://link.springer.com/article/10.1007/s42154-018-0023-y>

[3] Qin, H., Liu, Z., Liu, Y., et al.: A Two-level cross-sectional optimization approach for automotive body concept design. *Automot. Innov.* **1**(2), 122-130(2018)

<https://link.springer.com/article/10.1007/s42154-018-0022-z>

[4] Gao, F., Ren, S., Lin, C., et al.: Metamodel-based multi-objective reliable optimization for front structure of electric vehicle. *Automot. Innov.* **1**(2), 131-139(2018)

<https://link.springer.com/article/10.1007/s42154-018-0018-8>

[5] Peng, B., Zhang, H., Xuan, F., et al.: Torque distribution strategy of electric vehicle with in-wheel motors

based on the identification of driving intention. *Automot. Innov.* **1**(2), 140-146(2018)

<https://link.springer.com/article/10.1007/s42154-018-0024-x>

[6] Zhu, C., Zhu, P., Liu, Z., et al.: Prediction of the Elastic Properties of a Plain Woven Carbon Fiber Reinforced Composite with Internal Geometric Variability. *Automot. Innov.* **1**(2), 147-157(2018)

<https://link.springer.com/article/10.1007/s42154-018-0015-y>

[7] Mo, C., Li, Y., Zheng, L.: Simulation and analysis on overtaking safety assistance system based on vehicle-to-vehicle communication. *Automot. Innov.* **1**(2), 158-166(2018)

<https://link.springer.com/article/10.1007/s42154-018-0017-9>

[8] Zuo, S., Ni, T., Wu, X., et al.: Mechanism and conditions of the polygonal wear of vehicle tire. *Automot. Innov.* **1**(2), 167-176(2018)

<https://link.springer.com/article/10.1007/s42154-018-0016-x>

[9] Mu, Y., Li, L., Shi, S.: Modified tire-slip-angle model for chaotic vehicle steering motion. *Automot. Innov.* **1**(2), 177-186 (2018)

<https://link.springer.com/article/10.1007/s42154-018-0019-7>

Volume 1, Issue 1, 2018

[1] Li, J., Cheng, H., Guo, H., et al.: Survey on artificial intelligence for vehicles. *Automot. Innov.* **1**(1), 2-14 (2018)

<https://link.springer.com/article/10.1007/s42154-018-0034-8>

[2] Wang, Y., Zhao, F., Yuan, Y., et al.: Analysis of typical automakers' strategies for meeting the dual-credit regulations regarding CAFC and NEVs. *Automot. Innov.* **1**(1), 15-23(2018)

<https://link.springer.com/article/10.1007/s42154-018-0010-3>

[3] Ma, F., Zhao, Y., Liang, H., et al: Effects of cell microtopology on the in-plane dynamic crushing analysis of re-entrant square cellular material. *Automot. Innov.* **1**(1) ,24-34(2018)

<https://link.springer.com/article/10.1007/s42154-018-0005-0>

[4] Küçükay, F., Lange, A., Li, L.: Highly fuel-efficient transmission and propulsion concepts. *Automot. Innov.* **1**(1), 35-42(2018)

<https://link.springer.com/article/10.1007/s42154-018-0004-1>

[5] Li, L., Gong, Y., Deng, J., et al.: CO₂ reduction request and future high-efficiency zero-emission Argon power cycle engine. *Automot. Innov.* **1**(1), 43-53(2018)

<https://link.springer.com/article/10.1007/s42154-018-0007-y>

[6] Huang, K., Yan, Y., Li, B., et al.: A novel design of thermoelectric generator for automotive waste heat recovery. *Automot. Innov.* **1**(1), 54-61(2018)

<https://link.springer.com/article/10.1007/s42154-018-0006-z>

[7] Huang, Y., Khazeraee, M., Wang, H., et al.: Design of a regenerative auxiliary power system for service vehicles. *Automot. Innov.* **1**(1), 62-69(2018)

<https://link.springer.com/article/10.1007/s42154-018-0008-x>

[8] Lu, H., Zhang, J., Tian, N., et al.: Recycle-friendly aluminum alloy sheets for automotive applications based on hemming. *Automot. Innov.* **1**(1), 70-75(2018)

<https://link.springer.com/article/10.1007/s42154-018-0012-1>

[9] Takeda, A., Kondo, M., Mimuro, T.: Evaluation of the effectiveness of awareness messages for road traffic hazards in experimental tests. *Automot. Innov.* **1**(1), 76-84(2018)

<https://link.springer.com/article/10.1007/s42154-018-0011-2>

- [10] Lu, S., Cen, S., Zhang, Y.: Driver model-based fault-tolerant control of independent driving electric vehicle suffering steering failure. *Automot. Innov.* **1**(1), 85–94 (2018)
<https://link.springer.com/article/10.1007/s42154-018-0013-0>

Articles Listed by Technical Field

1. Intelligent Vehicles

- [1] Zhao, Y., Geng, H., Liang, J. et al.: Effects of driver response time under take-over control based on CAR-ToC model in human–machine mixed traffic flow. *Automot. Innov.* **6**(1), 3–19 (2023)
<https://doi.org/10.1007/s42154-022-00207-y>
- [2] Li, G., Wu, X., Eichberger, A. et al.: Drivers' EEG responses to different distraction tasks. *Automot. Innov.* **6**(1), 20–31 (2023)
<https://doi.org/10.1007/s42154-022-00206-z>
- [3] Wu, Y., Zhang, J., Li, W. et al. Towards human-vehicle interaction: driving risk analysis under different driver vigilance states and driving risk detection method. *Automot. Innov.* **6**(1), 32–47 (2023)
<https://doi.org/10.1007/s42154-022-00209-w>
- [4] Li, M., Jiang, C., Song, X. et al.: Parameter effects of the potential-field-driven model predictive controller for shared control. *Automot. Innov.* **6**(1), 48–61 (2023)
<https://doi.org/10.1007/s42154-022-00189-x>
- [5] Zhang, C., Huang, W., Niu, T. et al.: Review of clustering technology and its application in coordinating vehicle subsystems. *Automot. Innov.* **6**(1), 89–115 (2023)
<https://doi.org/10.1007/s42154-022-00205-0>
- [6] He, Y., Jin, L., Guo, B. et al. Density-Based Road Segmentation Algorithm for Point Cloud Collected by Roadside LiDAR. *Automot. Innov.* **6**(1), 116–130 (2023)
<https://doi.org/10.1007/s42154-022-00212-1>
- [7] Yin, Y., Li, S.E., Tang, K. et al.: Approximate optimal filter design for vehicle system through Actor-Critic Reinforcement Learning. *Automot. Innov.* **5**(4), 415–426 (2022)
<https://link.springer.com/article/10.1007/s42154-022-00195-z>
- [8] Guo, N., Zhang, X. & Zou, Y.: Real-time predictive control of path following to stabilize autonomous electric vehicles under extreme drive conditions. *Automot. Innov.* **5**(4), (2022)
<https://link.springer.com/article/10.1007/s42154-022-00202-3>
- [9] Tian, C., Leng, B., Hou, X. et al.: Robust identification of road surface condition based on ego-vehicle trajectory reckoning. *Automot. Innov.* **5**(4), 376–387 (2022)
<https://link.springer.com/article/10.1007/s42154-022-00196-y>
- [10] Tong, Y., Li, C., Wang, G. et al. Integrated Path-Following and Fault-Tolerant Control for Four-Wheel Independent-Driving Electric Vehicles. *Automot. Innov.* **5**(3), 311–323 (2022)
<https://link.springer.com/article/10.1007/s42154-022-00187-z>
- [11] Sun, P., Wang, Y., He, P. et al. GCD-L: A Novel Method for Geometric Change Detection in HD Maps Using Low-Cost Sensors. *Automot. Innov.* **5**(3), 324–332 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00188-y>

- [12] Chen, W., Tian, W., Xie, X. et al.: RGB Image- and Lidar-Based 3D Object Detection Under Multiple Lighting Scenarios. *Automot. Innov.* **5**(3), 251–259 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00176-2>

- [13] Jiang, K., Shi, Y., Zhou, T. et al.: PTMOT: A Probabilistic Multiple Object Tracker Enhanced by Tracklet Confidence for Autonomous Driving. *Automot. Innov.* **5**(3), 260–271 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00185-1>

- [14] Wang, W., Yu, S., Cao, W. et al.: Review of In-Vehicle Optical Fiber Communication Technology. *Automot. Innov.* **5**(3), 272–284 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00184-2>

- [15] Scheer, R., Bergheim, Y., Aleff, S. et al.: A Virtual Prototyping Approach for Development of PMSM on Real-Time Platforms: A Case Study on Temperature Sensitivity. *Automot. Innov.* **5**(3), 285–298 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00186-0>

- [16] Zhang, P., Zhu, B., Zhao, J. et al.: Performance Evaluation Method for Automated Driving System in Logical Scenario. *Automot. Innov.* **5**(3), 299–310 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00191-3>

- [17] Hoss, M., Scholtes, M. & Eckstein, L.: A Review of Testing Object-Based Environment Perception for Safe Automated Driving. *Automot. Innov.* **5**(3), 223–250 (2022)

<https://link.springer.com/article/10.1007/s42154-021-00172-y>

- [18] Chen, W., Tian, W., Xie, X. et al.: RGB Image- and Lidar-Based 3D Object Detection Under Multiple Lighting Scenarios. *Automot. Innov.* **5**(3), 251–259 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00176-2>

- [19] Jiang, K., Shi, Y., Zhou, T. et al.: PTMOT: A Probabilistic Multiple Object Tracker Enhanced by Tracklet Confidence for Autonomous Driving. *Automot. Innov.* **5**(3), 260–271 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00185-1>

- [20] Lu, H., Lu, C., Yu, Y. et al.: Autonomous overtaking for intelligent vehicles considering social preference based on hierarchical reinforcement learning. *Automot. Innov.* **5**(2), 195–208 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00177-1>

- [21] Wijaya, B., Jiang, K., Yang, M. et al.: Crowdsourced road semantics mapping based on pixel-wise confidence level. *Automot. Innov.* **5**(1) (2022)

<https://link.springer.com/article/10.1007/s42154-021-00173-x>

- [22] Zhao, Y., Tian, W. & Cheng, H.: Pyramid Bayesian Method for model uncertainty evaluation of semantic segmentation in autonomous driving. *Automot. Innov.* **5**(1) (2022)

<https://link.springer.com/article/10.1007/s42154-021-00165-x>

- [23] Gao, F., Mu, J., Han, X. et al.: Performance limit evaluation strategy for automated driving systems. *Automot. Innov.* **5**(1) (2022)

<https://link.springer.com/article/10.1007/s42154-021-00168-8>

- [24] Wang, Y., Cao, X. & Ma, X.: Evaluation of automatic lane-change model based on vehicle cluster generalized dynamic system. *Automot. Innov.* **5**(1) (2022)

<https://link.springer.com/article/10.1007/s42154-021-00171-z>

- [25] Peng, L., Wang, H. & Li, J.: Uncertainty evaluation of object detection algorithms for autonomous vehicles. *Automot. Innov.* **4**(3), 241–252 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00154-0>

- [26] Wang, Y., Wang, Y., Qin, H. et al.: A systematic risk assessment framework of automotive cybersecurity. *Automot. Innov.* **4**(3), 253–261 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00140-6>

- [27] Zhang, D., Lv, C., Yang, T. et al.: Cyber-attack detection for autonomous driving using vehicle dynamic state estimation. *Automot. Innov.* **4**(3), 262–273 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00153-1>

- [28] Quante, L., Zhang, M., Preuk, K. et al.: Human performance in critical scenarios as a benchmark for highly automated vehicles. *Automot. Innov.* **4**(3), 274–283 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00152-2>

- [29] Liang, Y., Li, Y., Yu, Y. et al.: Path-following control of autonomous vehicles considering coupling effects and multi-source system uncertainties. *Automot. Innov.* **4**(3), 284–300 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00155-z>

- [30] Biddle, L., Fallah, S.: A novel fault detection, identification and prediction approach for autonomous vehicle controllers using SVM. *Automot. Innov.* **4**(3), 301–314 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00138-0>

- [31] Hu, J., Cai, S., Huang, T. et al.: Vehicle travel destination prediction method based on multi-source data. *Automot. Innov.* **4**(3), 315–327 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00136-2>

- [32] Peng, B., Sun, Q., Li, S.E. et al.: End-to-end autonomous driving through dueling double Deep Q-Network. *Automot. Innov.* **4**(3), 328–337 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00151-3>

- [33] Tang, J., Zhou, Q.: A computer graphics-based framework for 3D pose estimation of pedestrians. *Automot. Innov.* **4**(3), 338–349 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00142-4>

- [34] Ma, F.W., Wang, J.W., Yang, Y., et al.: Stability design for the homogeneous platoon with communication time delay. *Automot. Innov.* **3**(2): 101–110 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00102-4>

- [35] Liu, W.M., Yao, N.L., Shi, Y.W., et al.: Personality openness predicts driver trust in automated driving. *Automot. Innov.* **3**(1): 3–13 (2020)

<https://link.springer.com/article/10.1007/s42154-019-00086-w>

- [36] Clark, J.R., Stanton, N.A., Revell, K.M.A. : Automated vehicle handover interface design: focus groups with learner, intermediate and advanced drivers. *Automot. Innov.* **3**(1): 14–29 (2020)

<https://link.springer.com/article/10.1007/s42154-019-00085-x>

- [37] Allison, C.K., Stanton, N.A.: Constraining design: applying the insights of cognitive work analysis to the design of novel in-car interfaces to support eco-driving. *Automot. Innov.* **3**(1): 30–41 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00090-5>

- [38] Brown, J. W. H., Stanton, N. A., Revell, K. M. A. : Usability assessment of steering wheel control interfaces in motorsport. *Automot. Innov.* **3**(1): 42–52 (2020)
<https://link.springer.com/article/10.1007/s42154-020-00088-z>
- [39] Terken, J., Pfleger, B.: Toward shared control between automated vehicles and users. *Automot. Innov.* **3**(1): 53–61 (2020)
<https://link.springer.com/article/10.1007/s42154-019-00087-9>
- [40] Xue, W.Y., Zheng, L.: Active collision avoidance system design based on model predictive control with varying sampling time. *Automot. Innov.* **3**(1): 62–72 (2020)
<https://link.springer.com/article/10.1007/s42154-019-00084-y>
- [41] Wang, Y. Y., Pan, D., Deng, H. Y., et al.: Dynamic trajectory planning of autonomous lane change at medium and low speeds based on elastic soft constraint of the safety domain. *Automot. Innov.* **3**(1): 73–87 (2020)
<https://link.springer.com/article/10.1007/s42154-020-00091-4>
- [42] Zhuang, W. C., Xu, L. W., Yin, G. D.: Robust cooperative control of multiple autonomous vehicles for platoon formation considering parameter uncertainties. *Automot. Innov.* **3**(1): 88–100 (2020)
<https://link.springer.com/article/10.1007/s42154-020-00093-2>
- [43] Yang, D., Jiao, X., Jiang, K. et al.: Driving space for autonomous vehicles. *Automot. Innov.* **2**(4): 241–253 (2019)
<https://link.springer.com/article/10.1007/s42154-019-00081-1>
- [44] Li, J., Cheng, H., Guo, H., et al.: Survey on artificial intelligence for vehicles. *Automot. Innov.* **1**(1), 2–14 (2018)
<https://link.springer.com/article/10.1007/s42154-018-0034-8>
- [45] Cai, Y., Zhang, T., Wang, H. et al.: 3D vehicle detection based on LiDAR and camera fusion. *Automot. Innov.* **2**(4): 276–283 (2019)
<https://link.springer.com/article/10.1007/s42154-019-00083-z>
- [46] Luo, Y., Yang, G., Xu, M., et al.: Cooperative lane-change maneuver for multiple automated vehicles on a highway. *Automot. Innov.* **2**(3), 157–168 (2019)
<https://link.springer.com/article/10.1007/s42154-019-00073-1>
- [47] Ge, L., Ma, F., Shi, J., et al.: Numerical implementation of high-order Vold–Kalman filter using Python arbitrary-precision arithmetic library. *Automot. Innov.* **2**(3), 178–189 (2019)
<https://link.springer.com/article/10.1007/s42154-019-00065-1>
- [48] Gao, Z., Li, Z., Hu, H., et al.: Experimental and numerical study of cervical muscle contraction in frontal impact. *Automot. Innov.* **2**(2), 93–101 (2019)
<https://link.springer.com/article/10.1007/s42154-019-00060-6>
- [49] Mimuro, T., Taniguchi, N. & Takanashi, H.: Concept study of a self-localization system for snow-covered roads using a four-layer laser scanner. *Automot. Innov.* **2**(2), 110–120 (2019)
<https://link.springer.com/article/10.1007/s42154-019-00061-5>
- [50] Wang, D., Wen, J., Wang, Y., et al.: End-to-end self-driving using deep neural networks with multi-auxiliary tasks. *Automot. Innov.* **2**(2), 127–136 (2019)
<https://link.springer.com/article/10.1007/s42154-019-00057-1>
- [51] Mo, C., Li, Y., Zheng, L.: Simulation and analysis on overtaking safety assistance system based on vehicle-to-vehicle communication. *Automot. Innov.* **1**(2), 158–166 (2018)

<https://link.springer.com/article/10.1007/s42154-018-0017-9>

- [52] Qiu, L., Qian, L., Abdollahi, Z., et al.: Engine-map-based predictive fuel-efficient control strategies for a group of connected vehicles. *Automot. Innov.* **1**(4), 311–319(2018)
<https://link.springer.com/article/10.1007/s42154-018-0042-8>
- [53] Guo, Y., Kumazawa, I., Kaku, C.: Blind spot obstacle detection from monocular camera images with depth cues extracted by CNN. *Automot. Innov.* **1**(4), 362–373 (2018)
<https://link.springer.com/article/10.1007/s42154-018-0036-6>
- [54] Patel, T.M., Bhatt, N.M.: Optimizing neural network parameters using taguchi's design of experiments approach: an application for equivalent stress prediction model of automobile chassis. *Automot. Innov.* **1**(4), 381–389(2018)
<https://link.springer.com/article/10.1007/s42154-018-0045-5>
- [55] Takeda, A., Kondo, M., Mimuro, T.: Evaluation of the effectiveness of awareness messages for road traffic hazards in experimental tests. *Automot. Innov.* **1**(1), 76–84(2018)
<https://link.springer.com/article/10.1007/s42154-018-0011-2>
- [56] Li, G., Li, S., Li, S. et al.: Deep reinforcement learning enabled decision-making for autonomous driving at intersections. *Automot. Innov.* **4**(3), 374–385 (2020)
<https://link.springer.com/article/10.1007/s42154-020-00113-1>
- [57] Chen, S., Chen, H. & Negrut, D.: Implementation of MPC-based path tracking for autonomous vehicles considering three vehicle dynamics models with different fidelities. *Automot. Innov.* **4**(3), 386–399 (2020)
<https://link.springer.com/article/10.1007/s42154-020-00118-w>
- [58] Meyer, M.A., Sauter, L., Granrath, C. et al.: Simulator coupled with distributed co-simulation protocol for automated driving tests. *Automot. Innov.* **4**(4), 373–389 (2021)
<https://link.springer.com/article/10.1007/s42154-021-00161-1>
- [59] Chen, G., Chen, K., Zhang, L. et al.: VCANet: vanishing-point-guided context-aware network for small road object detection. *Automot. Innov.* **4**(4), 400–412 (2021)
<https://link.springer.com/article/10.1007/s42154-021-00157-x>
- [60] Zhang, L., Meng, Q., Chen, H. et al.: Kalman Filter-based fusion estimation method of steering feedback torque for steer-by-wire systems. *Automot. Innov.* **4**(4), 430–439 (2021)
<https://link.springer.com/article/10.1007/s42154-021-00159-9>

2. Electric Vehicles

Drive System

- [1] Wang, J., Gao, S., Qiang, Y. et al.: Structural topology and dynamic response analysis of an electric torque vectoring drive-axle for electric vehicles. *Automot. Innov.* **5**(2), 164–179 (2022)
<https://link.springer.com/article/10.1007/s42154-022-00178-0>
- [2] Lin, C., Yu, X., Zhao, M. et al.: Collaborative control of novel uninterrupted propulsion system for all-climate electric vehicles. *Automot. Innov.* **5**(1) (2022)
<https://link.springer.com/article/10.1007/s42154-021-00170-0>
- [3] Liu, Y., Chen, L., Cai, T. et al.: Dual-pump control algorithm of two-speed powershift transmissions in electric vehicles. *Automot. Innov.* **5**(1) (2022)

<https://link.springer.com/article/10.1007/s42154-021-00160-2>

[4] Qin, Y., Zhao, Z., Wang, Z. et al.: Study of longitudinal–vertical dynamics for in-wheel motor-driven electric vehicles. *Automot. Innov.* **4**(2), 227–237 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00141-5>

[5] Cai, W., Wu, X., Zhou, M. et al.: Review and development of electric motor systems and electric powertrains for new energy vehicles. *Automot. Innov.* **4**(1), 3–22 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00139-z>

[6] Chen, H., Li, L. & Küçükay, F.: Study of series-parallel and power-split DHT for hybrid powertrains. *Automot. Innov.* **4**(1), 23–33 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00126-w>

[7] Xu, X., Liang, J., Hao, Q. et al.: A novel electric dual motor transmission for heavy commercial vehicles. *Automot. Innov.* **4**(1), 34–43 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00129-7>

[8] Wang, W., Zhang, Y., Sun, X. et al.: Model-based double closed-loop coordinated control strategy for the electro-mechanical transmission system of heavy power-split HEVs. *Automot. Innov.* **4**(1), 44–55 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00130-0>

[9] Qi, B., Yang, L., Zhang, L. et al.: Adaptive fault-tolerant control during the mode switching for electric vehicle dual-mode coupling drive system. *Automot. Innov.* **4**(1), 56–69 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00132-y>

[10] Dorsch, C., Wang, X. & Küçükay, F.: Objective rating of the launch behavior of conventional, hybrid and electric vehicles. *Automot. Innov.* **4**(1), 70–80 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00131-z>

[11] Wang, W., Durack, J.M., Durack, M.J. et al.: Automotive traction drive speed reducer efficiency testing. *Automot. Innov.* **4**(1), 81–92 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00135-3>

[12] Hu, J., Wei, Z. & He, H.: An online adaptive internal short circuit detection method of lithium-ion battery. *Automot. Innov.* **4**(1), 93–102 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00127-9>

[13] Che, Y., Foley, A., El-Gindy, M. et al.: Joint estimation of inconsistency and state of health for series battery packs. *Automot. Innov.* **4**(1), 103–116 (2021)

<https://link.springer.com/article/10.1007/s42154-020-00128-8>

[14] Tian, F., Sui, L., Zeng, Y., et al.: Hardware design and test of a gear-shifting control system of a multi-gear transmission for electric vehicles. *Automot. Innov.* **2**(3), 212-222 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00072-2>

[15] Dong, Y., Chen, Y., Yu, C., et al.: Performance of the transmission parking mechanism of a battery electric vehicle simulated with Adams software. *Automot. Innov.* **1**(2), 114-121(2018)

<https://link.springer.com/article/10.1007/s42154-018-0023-y>

[16] Wang, C., Lian, Y., Ling, H., et al.: Multiphysics field co-simulation research based on electric drive system for a specific type of car. *Automot. Innov.* **2**(3), 223-230 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00067-z>

[17] Zhang, S.: Parameter study and improvement of gearbox whine noise in electric vehicle. *Automot. Innov.* **1**(3), 272-280(2018)

<https://link.springer.com/article/10.1007/s42154-018-0029-5>

[18] Xu, X., Sun, W., Cai, T., et al.: Design of a hydraulic control unit for a two-speed dedicated electric vehicle transmission. *Automot. Innov.* **1**(4), 300-310(2018)

<https://link.springer.com/article/10.1007/s42154-018-0039-3>

[19] Li, L., Chen, H. & Küçükay, F.: Systematic synthesis of dedicated hybrid transmission. *Automot. Innov.* **2**(3), 231-239 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00071-3>

[20] Peng, B., Zhang, H., Xuan, F., et al.: Torque distribution strategy of electric vehicle with in-wheel motors based on the identification of driving intention. *Automot. Innov.* **1**(2), 140-146(2018)

<https://link.springer.com/article/10.1007/s42154-018-0024-x>

[21] Qin, D., Cheng, L., Wang, T., et al.: Modeling and testing of the multi-pole field of a motor for pure electric vehicles. *Automot. Innov.* **1**(3), 226-236 (2018)

<https://link.springer.com/article/10.1007/s42154-018-0025-9>

[22] Hengst, J., Werra, M. & Küçükay, F.: Evaluation of transmission losses of various battery electric vehicles. *Automot. Innov.* **5**(4), 388-399 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00194-0>

Others

[23] Kong, W., Cai, T., Luo, Y. et al.: Energy management optimization based on aging adaptive functional state model of battery for internal combustion engine vehicles. *Automot. Innov.* **6**(1), 62–75 (2023)

<https://doi.org/10.1007/s42154-022-00204-1>

[24] Zhang, L., Ning, L., Yang, X. et al. Half-Power Prediction and Its Application on the Energy Management Strategy for Fuel Cell City Bus. *Automot. Innov.* **6**(1), 131–142 (2023)

<https://doi.org/10.1007/s42154-022-00210-3>

[25] Yang, N., Song, Z., Amini, M.R. et al.: Internal short circuit detection for parallel-connected battery cells using Convolutional Neural Network. *Automot. Innov.* **5**(2), 107–120 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00180-6>

[26] Liu, K., Peng, Q., Li, K. et al.: Data-based interpretable modeling for property forecasting and sensitivity analysis of Li-ion battery electrode. *Automot. Innov.* **5**(2), 121–133 (2022)

<https://link.springer.com/article/10.1007/s42154-021-00169-7>

[27] Huang, H., Meng, J., Wang, Y. et al.: An enhanced data-driven model for lithium-ion battery state-of-health estimation with optimized features and prior knowledge. *Automot. Innov.* **5**(2), 134–145 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00175-3>

[28] Cao, R., Cheng, H., Jia, X. et al.: Non-invasive characteristic curve analysis of lithium-ion batteries enabling degradation analysis and data-driven model construction: a review. *Automot. Innov.* **5**(2), 146–163 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00181-5>

[29] Lin, C., Kong, W., Tian, Y. et al.: Heating lithium-ion batteries at low temperatures for onboard applications: recent progress, challenges and prospects. *Automot. Innov.* **5**(1) (2022)

<https://link.springer.com/article/10.1007/s42154-021-00166-w>

[30] Wang, Z., Li, L., Deng, J. et al.: Magnetic coupler robust optimization design for electric vehicle wireless charger based on improved simulated annealing algorithm. *Automot. Innov.* **5**(1) (2022)

<https://link.springer.com/article/10.1007/s42154-021-00167-9>

[31] Xue, Q., Yang, D., Jiang, L. et al.: Modifying carbon supports of catalyst for the oxygen reduction reaction in vehicle PEMFCs. *Automot. Innov.* **4**(2), 119–130 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00149-x>

[32] Du, L., Zhang, G. & Sun, S.: Proton Exchange Membrane (PEM) fuel cells with Platinum Group Metal (PGM)-free cathode. *Automot. Innov.* **4**(2), 131–143 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00146-0>

[33] Wang, H., Wang, R., Sui, S. et al.: Cathode design for Proton Exchange Membrane fuel cells in automotive applications. *Automot. Innov.* **4**(2), 144–164 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00148-y>

[34] Yin, C., Gao, Y., Li, K. et al.: Experimental investigation on local behaviors of PEMFC with segmented cell. *Automot. Innov.* **4**(2), 165–175 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00145-1>

[35] Wu, G., Zhang, H., Xu, Y. et al.: Air-side fin geometry of a tube-strip heat exchanger for fuel cell vehicles. *Automot. Innov.* **4**(2), 176–188 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00147-z>

[36] Li, G., Liu, C., Wang, E. et al.: State of charge estimation for lithium-ion battery based on improved cubature kalman filter algorithm. *Automot. Innov.* **4**(2), 189–200 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00134-4>

[37] Bai, X., Chen, G., Li, W. et al.: Critical speeds of electric vehicles for regenerative braking. *Automot. Innov.* **4**(2), 201–214 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00143-3>

[38] Hao, D., Wang, X.B., Zhang, Y.Y., et al.: Experimental study on hydrogen leakage and emission of fuel cell vehicles in confined spaces. *Automot. Innov.* **3**(2): 111–122 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00096-z>

[39] Mao, W.F., Yue, W., Pei, F., et al.: Manganese-based lithium-ion battery: Mn₃O₄ anode versus LiNi_{0.5}Mn_{1.5}O₄ cathode. *Automot. Innov.* **3**(2): 123–132 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00100-6>

[40] Qin, Y., Wang, Z., Yuan, K. et al.: Comprehensive analysis and optimization of dynamic vibration-absorbing structures for electric vehicles driven by in-wheel motors. *Automot. Innov.* **2**(4): 254–262 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00079-9>

[41] Han, X., Feng, X., Ouyang, M. et al.: A comparative study of charging voltage curve analysis and state of health estimation of lithium-ion batteries in electric vehicle. *Automot. Innov.* **2**(4): 263–275 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00080-2>

[42] Wang, Y., Zhao, F., Yuan, Y., et al.: Analysis of typical automakers' strategies for meeting the dual-credit regulations regarding CAFC and NEVs. *Automot. Innov.* **1**(1), 15–23(2018)

<https://link.springer.com/article/10.1007/s42154-018-0010-3>

[43] Zhao, B., Lv, C. & Hofman, T.: Driving-cycle-aware energy management of hybrid electric vehicles using a three-dimensional Markov chain model. *Automot. Innov.* **2**(2), 146–156 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00059-z>

[44] Qin, D., Li, J., Wang, T., et al.: Modeling and simulating a battery for an electric vehicle based on Modelica.

Automot. Innov. **2**(3), 169-177 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00066-0>

[45] Lu, S., Cen, S., Zhang, Y.: Driver model-based fault-tolerant control of independent driving electric vehicle suffering steering failure, Automot. Innov. **1**(1), 85-94 (2018)

<https://link.springer.com/article/10.1007/s42154-018-0013-0>

[46] Yao, C., Dan, D., Zhang, Y. et al.: Thermal performance of a micro heat pipe array for battery thermal management under special vehicle-operating conditions. Automot. Innov. **4**(3), 317–327 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00114-0>

[47] Shen, M., Gao, Q.: Simulation and analysis of dual-evaporator refrigeration system for electric vehicles. Automot. Innov. **4**(3), 347–355 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00115-z>

[48] Wu, X., Wang, J., Zhang, Y. et al.: Review of DC-DC converter topologies based on impedance network with wide input voltage range and high gain for fuel cell vehicles. Automot. Innov. **4**(4), 351–372 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00163-z>

[49] Wen, X., Li, Y., Yang, C.: Design, modeling, and characterization of a tubular linear vibration energy harvester for integrated active wheel system. Automot. Innov. **4**(4), 413–429 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00144-2>

[50] Li, J., He, H., Wei, Z. et al.: Hierarchical sizing and power distribution strategy for hybrid energy storage system. Automot. Innov. **4**(4), 440–447 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00164-y>

[51] Huang, Y., Yang, S., Zhou, S. et al.: An innovative state-of-charge estimation method of lithium-ion battery based on 5th-order Cubature Kalman Filter. Automot. Innov. **4**(4), 448–458 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00162-0>

[52] Zhang, B., Hao, D., Chen, J. et al. Modeling and Decentralized Predictive Control of Ejector Circulation-Based PEM Fuel Cell Anode System for Vehicular Application. Automot. Innov. **5**(3), 333–345 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00190-4>

[53] Chu, X., Xue, F., Liu, T. et al.: Adaptive fitting capacity prediction method for lithium-ion batteries. Automot. Innov. **5**(4), 359-375 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00201-4>

[54] Yang, S., Cheng, H., Wang, M. et al.: Multi-scale battery modeling method for fault diagnosis. Automot. Innov. **5**(4), 400-414 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00197-x>

[55] Gao, M., Chen, L., Ma, T. et al.: Comparative study on traction battery charging strategies from the perspective of material structure. Automot. Innov. **5**(4), 427-437 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00199-9>

[56] Gao, Y., Yang, S., Wang, X. et al.: Cyber hierarchy multiscale integrated energy management of intelligent hybrid electric vehicles. Automot. Innov. **5**(4), 438-452 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00200-5>

3. Car Body Design & Lightweight

Car Body Design

[1] Liu, X., Liang, M. & Luo, Q.: Innovative electric vehicle body design based on insurance institute for highway safety side impact conditions. *Automot. Innov.* **2**(3), 201-211 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00070-4>

[2] Ou, H., Tang, X., Xiao, J., et al.: Lightweight body-in-white design driven by optimization technology. *Automot. Innov.* **1**(3), 255-262(2018)

<https://link.springer.com/article/10.1007/s42154-018-0032-x>

[3] Zhou, J., Feng, L., Chen, J., et al.: Uncertainty optimization design of a vehicle body structure considering random deviations. *Automot. Innov.* **1**(4), 342-351(2018)

<https://link.springer.com/article/10.1007/s42154-018-0041-9>

[4] Qin, H., Liu, Z., Liu, Y., et al.: A two-level cross-sectional optimization approach for automotive body concept design. *Automot. Innov.* **1**(2), 122-130(2018)

<https://link.springer.com/article/10.1007/s42154-018-0022-z>

[5] Gao, F., Ren, S., Lin, C., et al.: Metamodel-based multi-objective reliable optimization for front structure of electric vehicle. *Automot. Innov.* **1**(2), 131-139(2018)

<https://link.springer.com/article/10.1007/s42154-018-0018-8>

Lightweight Materials

[6] Rosenthal, S., Maaß, F., Kamaliev, M. et al.: Lightweight in automotive components by forming technology. *Automot. Innov.* **3**(3), 195–209 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00103-3>

[7] Sun, Y., Luzin, V., Duan, Y. et al.: Forming-induced residual stress and material properties of roll-formed high-strength steels. *Automot. Innov.* **3**(3), 210–220 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00112-2>

[8] Li, M., Wang, Y., Niu, Z. et al.: Study on the weld-bonding process optimization and mechanical performance of aluminum alloy joints. *Automot. Innov.* **3**(3), 221–230 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00106-0>

[9] Cui, J., Wang, S., Yuan, W. et al.: Effects of standoff distance on magnetic pulse welded joints between aluminum and steel elements in automobile body. *Automot. Innov.* **3**(3), 231–241 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00104-2>

[10] Ma, Y., Niu, S., Shan, H. et al.: Impact of stack orientation on self-piercing riveted and friction self-piercing riveted Aluminum alloy and Magnesium alloy joints. *Automot. Innov.* **3**(3), 242–249 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00108-y>

[11] Wang, D., Xie, C., Liu, Y. et al.: Multi-objective collaborative optimization for the lightweight design of an electric bus body frame. *Automot. Innov.* **3**(3), 250–259 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00105-1>

[12] Shi, Z., Chen, G., Zhu, L. et al.: Sandwich structure design of a cooling fin for battery modules against impact loads. *Automot. Innov.* **3**(3), 260–269 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00107-z>

[13] Li, J., Wang, L., Chen, Y. et al.: Research and application of lightweight index for passenger cars. *Automot. Innov.* **3**(3), 270–279 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00110-4>

[14] Lin, Y., Min, J., Teng, H. et al.: Flexural performance of steel–FRP composites for automotive applications. *Automot. Innov.* **3**(3), 280–295 (2020)
<https://link.springer.com/article/10.1007/s42154-020-00109-x>

[15] Ma, F., Ying, Z., Wang, G., et al.: Crashworthiness optimization design of thin-walled tube filled with re-entrant triangles honeycombs. *Automot. Innov.* **2**(1), 1-13 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00051-7>

[16] Shen, Q., Li, X., Zhao, Y., et al.: Experimental and performance analyses on elastomer-strengthened polyethylene terephthalate/glass fiber blends. *Automot. Innov.* **2**(1), 71-78(2019)

<https://link.springer.com/article/10.1007/s42154-019-00047-3>

[17] Wang, S., Min, J., Lin, J., et al.: Effect of atmospheric pressure plasma treatment on the lap-shear strength of adhesive-bonded sheet molding compound joints. *Automot. Innov.* **1**(3), 237-246(2018)

<https://link.springer.com/article/10.1007/s42154-018-0027-7>

[18] Zheng, G., Fan, Z., Zhang, H., et al.: Crashworthiness optimization of steel–magnesium hybrid double-hat-shaped tube. *Automot. Innov.* **1**(3), 247-254 (2018)

<https://link.springer.com/article/10.1007/s42154-018-0033-9>

[19] Zhu, C., Zhu, P., Liu, Z., et al.: Prediction of the Elastic Properties of a Plain Woven Carbon Fiber Reinforced Composite with Internal Geometric Variability. *Automot. Innov.* **1**(2), 147-157(2018)

<https://link.springer.com/article/10.1007/s42154-018-0015-y>

[21] Lu, H., Zhang, J., Tian, N., et al.: Recycle-friendly aluminum alloy sheets for automotive applications based on hemming. *Automot. Innov.* **1**(1), 70-75(2018)

<https://link.springer.com/article/10.1007/s42154-018-0012-1>

[22] Ma, F., Zhao, Y., Liang, H., et al: Effects of cell microtopology on the in-plane dynamic crushing analysis of re-entrant square cellular material. *Automot. Innov.* **1**(1) ,24-34(2018)

<https://link.springer.com/article/10.1007/s42154-018-0005-0>

4. Energy-saving and Eco-systems

Engine

[1] Noce, T., Hanriot, S.D.M., Sales, L.C.M., et al.: Energy conversion factor for gasoline engines in real-world driving emission cycle. *Automot. Innov.* **3**(2): 169–180 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00098-x>

[2] Neumann, D., Schäfers, L., Muthyalu, P., et al.: Reduction of transient engine-out NO_x-emissions by advanced digital combustion rate shaping. *Automot. Innov.* **3**(2): 181–190 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00101-5>

[3] Shuai, S., Ma, X., Li, Y., et al.: Recent progress in automotive gasoline direct injection engine technology. *Automot. Innov.* **1**(2), 95-113(2018)

<https://link.springer.com/article/10.1007/s42154-018-0020-1>

[4] Wu, Z., Zhao, W., Li, Z., et al.: A review of engine fuel injection studies using synchrotron radiation x-ray imaging. *Automot. Innov.* **2**(2), 79-92 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00056-2>

[5] Li, F., Wang, Z., Wang, Y. et al. High-efficiency and clean combustion natural gas engines for vehicles. *Automot. Innov.* **2**(4): 284–304 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00075-z>

[6] Dong, G., Li, L., Zhu, D. et al.: Ion current features of HCCI combustion in a GDI engine. *Automot. Innov.* **2**(4): 305–313 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00074-0>

[7] Zhao, Z., Meng, Z., Li, L. et al.: Experimental study on the combustion and energy flows of vehicle engine under NEDC of cold start. *Automot. Innov.* **2**(4): 314–327 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00078-w>

[8] Qi, Y., Wang, B. & Wang, Z.: Impact resistance of spark plug's ceramic insulator during ultra-high-pressure combustion under deto-knock conditions. *Automot. Innov.* **2**(2), 137-145 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00058-0>

[9] Li, L., Gong, Y., Deng, J., et al.: CO₂ reduction request and future high-efficiency zero-emission Argon power cycle engine. *Automot. Innov.* **1**(1), 43-53(2018)

<https://link.springer.com/article/10.1007/s42154-018-0007-y>

[10] Wu, J., Kang, Z., Zhang, Z., et al.: Effects of vessel and water temperatures on direct injection in internal combustion Rankine cycle engines. *Automot. Innov.* **1**(4), 331-341(2018)

<https://link.springer.com/article/10.1007/s42154-018-0046-4>

[11] Gong, H.: Estimation of residual exhaust gas of homogeneous charge compression ignition gasoline engine operating under negative valve overlap strategy. *Automot. Innov.* **2**(1), 45-54(2019)

<https://link.springer.com/article/10.1007/s42154-019-00048-2>

[12] Wang, C., Jin, S., Deng, J. et al.: An innovative Argon/Miller power cycle for internal combustion engine: thermodynamic analysis of its efficiency and power density. *Automot. Innov.* **6**(1), 76–88 (2023)

<https://doi.org/10.1007/s42154-022-00208-x>

Driveline

[13] Xu, X., Dong, P., Liu, Y., et al.: Progress in automotive transmission technology. *Automot. Innov.* **1**(3), 187-210 (2018)

<https://link.springer.com/article/10.1007/s42154-018-0031-y>

[14] Küçükay, F., Lange, A., Li, L.: Highly fuel-efficient transmission and propulsion concepts. *Automot. Innov.* **1**(1), 35-42(2018)

<https://link.springer.com/article/10.1007/s42154-018-0004-1>

[15] Shi, T., Zhao, F., Hao, H, et al.: Development trends of transmissions for hybrid electric vehicles using an optimized energy management strategy. *Automot. Innov.* **1**(4), 291-299(2018)

<https://link.springer.com/article/10.1007/s42154-018-0037-5>

[16] Zhu, M., Yao, P., Pu, Y..: Comparative study on the temperature rise of a dry dual clutch under different starting conditions. *Automot. Innov.* **2**(1), 35-44(2019)

<https://link.springer.com/article/10.1007/s42154-019-00053-5>

[17] Li, X., Lyu, J., Hong, J., et al.: MPC-based downshift control of automated manual transmissions. *Automot. Innov.* **2**(1), 55-63(2019)

<https://link.springer.com/article/10.1007/s42154-019-00050-8>

Others

[18] Liu, J., Li, J., Wang, Y., et al.: Technology development analysis on low carbon for power of heavy-duty commercial vehicle. *Automot. Innov.* **2**(1), 64-70(2019)

<https://link.springer.com/article/10.1007/s42154-019-00054-4>

[19] Yu, C., Ji, G., Zhang, C., et al.: Cost-efficient thermal management for a 48v li-ion battery in a mild hybrid electric vehicle. *Automot. Innov.* **1**(4), 320-330(2018)

<https://link.springer.com/article/10.1007/s42154-018-0043-7>

[20] Li, B., Kuo, H., Wang, X. et al.: Thermal management of electrified propulsion system for low-carbon vehicles. *Automot. Innov.* **4**(3), 299–316 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00124-y>

[21] Wang, G., Gao, Q., Yan, Y. et al.: Thermal management optimization of a lithium-ion battery module with graphite sheet fins and liquid cold plates. *Automot. Innov.* **4**(3), 336–346 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00121-1>

[22] Zhao, Z., Liu, W., Li, F. et al.: Distributed gas ignition using injection strategy for high efficiency and clean combustion under lean condition. *Automot. Innov.* **4**(3), 366–373 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00116-y>

[23] Wang, P., Xue, Q., Yang, J. et al.: Energy security planning for hydrogen fuel cell vehicles in large-scale events: a case study of Beijing 2022 Winter Olympics. *Automot. Innov.* **5**(2), 209–220 (2022)

<https://link.springer.com/article/10.1007/s42154-022-00183-3>

5. Vehicle Safety Technology

[1] Lei, Y.L., Song, P.X., Fu, Y.: Design of constant-speed control method for water medium hydraulic retarders based on neural network. *Automot. Innov.* **3**(2): 147–157 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00095-0>

[2] Ye, Z.S., Xie, W.D., Yin, Y.M., et al.: Dynamic rollover prediction of heavy vehicles considering critical frequency. *Automot. Innov.* **3**(2): 158–168 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00099-w>

[3] Zhang, X., Huang, Y., Guo, K., et al.: Integrated spacing policy considering micro- and macroscopic characteristics. *Automot. Innov.* **2**(2), 102-109 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00064-2>

[4] Lian, Y., Zeng, D., Ye, S., et al.: High-voltage safety improvement design for electric vehicle in rear impact. *Automot. Innov.* **1**(3), 211-225(2018)

<https://link.springer.com/article/10.1007/s42154-018-0030-z>

[5] Gawande, S. H., MuleyR, A. A., Yerrawar, N.: Optimization of torsional stiffness for heavy commercial vehicle chassis frame. *Automot. Innov.* **1**(4), 352-361(2018)

<https://link.springer.com/article/10.1007/s42154-018-0044-6>

[6] Yurchenko, N.F., Breed, D.S., Zhang, S.: Design of the airbag inflation system applicable to conventional and autonomous vehicles. *Automot. Innov.* **4**(4), 390–399 (2021)

<https://link.springer.com/article/10.1007/s42154-021-00156-y>

6. Others

[1] Xu, N., Yang, Y.Y., Guo, K.H.: A discrete tire model for cornering properties considering rubber friction.

Automot. Innov. **3**(2): 133–146 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00097-y>

[2] Liu, J., Huang, L., Zhou, R. et al.: Reliability growth test planning and verification of commercial vehicles.

Automot. Innov. **2**(4): 328-337(2019)

<https://link.springer.com/article/10.1007/s42154-019-00082-0>

[3] Wang, S., Guo, W., Zeng, K., et al.: Characterization of automotive brake discs with laser-machined surfaces.

Automot. Innov. **2**(3), 190-200 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00068-y>

[4] Yang, W.: Scale consistency quantification for subjective evaluation of vehicle dynamics. Automot. Innov.

2(2), 121-126 (2019)

<https://link.springer.com/article/10.1007/s42154-019-00062-4>

[5] Huang, K., Yan, Y., Li, B., et al.: A novel design of thermoelectric generator for automotive waste heat recovery. Automot. Innov. **1**(1), 54-61(2018)

<https://link.springer.com/article/10.1007/s42154-018-0006-z>

[6] Huang, Y., Khazeraee, M., Wang, H., et al.: Design of a regenerative auxiliary power system for service vehicles. Automot. Innov. **1**(1), 62-69(2018)

<https://link.springer.com/article/10.1007/s42154-018-0008-x>

[7] Zuo, S., Ni, T., Wu, X., et al.: Mechanism and conditions of the polygonal wear of vehicle tire. Automot. Innov. **1**(2), 167-176(2018)

<https://link.springer.com/article/10.1007/s42154-018-0016-x>

[8] Mu, Y., Li, L., Shi, S.: Modified tire-slip-angle model for chaotic vehicle steering motion. Automot. Innov. **1**(2), 177-186 (2018)

<https://link.springer.com/article/10.1007/s42154-018-0019-7>

[9] Shao, X., Xu, N., Liu, X.: Investigation and application on the vertical vibration models of the seated human body. Automot. Innov. **1**(3), 263-271(2018)

<https://link.springer.com/article/10.1007/s42154-018-0026-8>

[10] Pei, X., Hu, X., Liu, W., et al.: State estimation of vehicle's dynamic stability based on the nonlinear Kalman filter. Automot. Innov. **1**(3), 281-289(2018)

<https://link.springer.com/article/10.1007/s42154-018-0028-6>

[11] Michelotti, A.C., da Silva, J.C., Nicolazzi, L.C.: Novel mechanical interface design for automotive starting systems. Automot. Innov. **2**(1), 14-25(2019)

<https://link.springer.com/article/10.1007/s42154-019-00052-6>

[12] Yang, W., Chen, J., Liu, Z., et al: Vibration characteristics of framed SUV cab based on coupled transfer path analysis. Automot. Innov. **2**(1) ,26-34(2019)

<https://link.springer.com/article/10.1007/s42154-019-00049-1>

[13] Chen, W., Lu, C., Liu, Z., et al.: Simplified method of simulating double-layer micro-perforated panel structure. Automot. Innov. **1**(4), 374-380(2018)

<https://link.springer.com/article/10.1007/s42154-018-0040-x>

[14] Chen, Y., Yan, Y. & Li, B.: Thermal analyses of power electronics integrated with vapour chamber cooling. Automot. Innov. **4**(3), 328–335 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00123-z>

[15] Shah, R.M.R.A., Qubeissi, M.A., McGordon, A. et al.: Micro gas turbine range extender performance analysis

using varying intake temperature. *Automot. Innov.* **4**(3), 356–365 (2020)

<https://link.springer.com/article/10.1007/s42154-020-00119-9>